

# Data sheet

Wire type and power	DC 3-wire type 12-24VDC ---
Sensing side diameter	M08
Sensing distance	1.5mm
Installation	Flush
Standard sensing target	8×8×1mm(iron)
Response frequency	1.5kHz
Current specification	Current consumption: Max. 10mA
Control output	NPN Normally Open
Material	Case/Nut: Nickel plated Brass, (connector case of DIA. of sensing side $\varnothing$ 8 mm: SUS303), washer: Nickel plated Iron, sensing side: polybutylene terephthalate, standard cable (black): polyvinyl chloride (PVC), oil resistant cable (gray): oil resistant polyvinyl chloride (PVC)
Cable Standard/material	Standard cable
Protection structure	IP67(IEC standard)
Body length	Standard type
Environment_Ambient temperature	-25 to 70°C, storage: -30 to 80°C
Environment_Ambient humidity	35 to 95% RH, storage: 35 to 95% RH
Hysteresis(distance)	Max. 10% of sensing distance
Residual voltage	Max. 2V
Weight	Approx. 64g(approx. 52g)

※The response frequency is the average value. The standard sensing target is used and the width is set as 2 times of the standard sensing target, 1/2 of the sensing distance for the distance.

※The weight includes packaging. The weight in parenthesis is for unit only.

※The temperature or humidity mentioned in Environment indicates a non freezing or condensation.